

CEMO KS MOBIL EASY PG 4

WITH ADR APPROVAL

KS-MOBIL Easy 120 L, 190 L, 330 L approved for transport under ADR approval no. D/BAM 14341/31H2 (120 L and 190 L)

Examinations every 2½ years corresponding ADR 6.5.4.4.1 b*** and ADR 6.5.4.4.2 b. Completely assembled.

Container:

- single-walled 120 L, 190 L or 330 L
- electrically conductive highly cross-linked polyethylene
- patented flame suppressant filling (120 L and 190 L)
- with flashback arrester (330 L)
- dipstick for checking fill level (120 L and 190 L)
- with contents gauge (330 L)
- integral dispensing nozzle holder
- integral filling nozzle
- integral vent and pressure relief
- integral forklift pockets
- integral handles
- integral recesses for ratchet straps during transport

Pre-fitted pump:

- 25 L/min hand pump, 2.7 m filling hose (statically conductive) and manual nozzle
- self-priming pump 12 V DC 25 L/min or 230 V AC 40 L/min, ATEX-approved, automatic dispensing nozzle, 4 m filling hose (statically conductive) and 5 m electrical cable (pump 230 V without cable)

For optional digital K24 flow meter ATEX, installed between the filling hose and automatic nozzle for the version with electric pump, see p. 127



Petrol and petrol mixtures





Explosion-suppressing insert (patent protected), hence no explosive atmosphere inside the container (120 L and 190 L)





Flashback arrester (330 L)



KS-MOBIL Easy 120 L with pump 12V



KS-MOBIL Easy 330 L with pump 12V and hinged lid

Capacity / Description		Dimensions cm (I x w x h)	Weight approx. kg	Order no.
120L with hand pump		80 x 60 x 45	23	10091
120L with pump 12V, 25 L/min, ATEX and automatic nozzle	NEW	80 x 60 x 45	33	11498
120 L with hand pump and hinged lid		80 x 60 x 47	26	10092
120L with pump 12V, 25 L/min, ATEX, automatic nozzle and hinged lid	NEW	80 x 60 x 47	36	11499
190 L with hand pump		80 x 60 x 59	25	10093
190L with pump 12 V, 25 L/min, ATEX and automatic nozzle	NEW	80 x 60 x 59	35	11500
190 L with hand pump and hinged lid		80 x 60 x 61	28	10094
190L with pump 12 V, 25 L/min, ATEX, automatic nozzle and hinged lid	NEW	80 x 60 x 61	38	11501
190 L with pump 230 V, 40 L/min, ATEX and automatic nozzle		80 x 60 x 59	35	10458
330 L with pump 12 V, 25 L/min, ATEX, automatic nozzle and hinged lid	NEW	118 x 79 x 57	42	11502*

^{*} Available from September 2021

^{***} The transport approval for all plastic IBCs is limited to 5 years.