

SILKOLENE QUAD ATV 5W-40

Fully synthetic 4-Stroke oil for modern highly stressed Quads and ATVs

Description

Fuchs SILKOLENE QUAD ATV 5W-40 is a fully synthetic, four stroke, multigrade engine oil formulated for All Terrain Vehicles (ATVs) and Quad Bikes. SILKOLENE QUAD ATV 5W-40 provides excellent wear protection and engine cleanliness to ensure long term performance and reliability. It fully protects the engine from cold start to full power over a wide range of ambient temperature. Stay in grade capability ensures consistent performance for the full service life.

Advantages / Benefits

- Better wear protection
- Better high temperature deposit control
- Better low temperature fluidity
- Excellent wet clutch performance
- Better elastomer compatibility

Application

SILKOLENE QUAD ATV 5W-40 is recommended for all ATVs and Quad Bikes where SAE 15W-40, 10W-40 and 5W-40 oils are specified.

SILKOLENE QUAD ATV 5W-40 also helps to protect internal components during storage and periods on inactivity.

Specifications/Approvals

- | | |
|--------|-------|
| • API | SN |
| • ACEA | A3/B3 |
| • JASO | MA2 |

Typical Data: SILKOLENE QUAD ATV 5W-40

Characteristics	Test Method	Unit	Results
SAE Grade			5W-40
Appearance	Visual		Amber, clear and bright
Specific gravity at 15°C	IP160		0.857
Kinematic Viscosity at 40°C	IP71	mm ² /s	85.9
Kinematic Viscosity at 100°C	IP71	mm ² /s	14.4
Viscosity Index (VI)	IP226		174
Cold Crank Viscosity at -30°C	ASTM D5293	cP	6250
Pour point	IP15	°C	-35